

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
7 July 2005 (07.07.2005)

PCT

(10) International Publication Number
WO 2005/061118 A1

(51) International Patent Classification:
B01J 2/04

(74) Agent: ANDERSON, Elin; Norsk Hydro ASA, N-0240
Oslo (NO).

(21) International Application Number:
PCT/NO2003/000440

(22) International Filing Date:
23 December 2003 (23.12.2003)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): YARA
INTERNATIONAL [NO/NO]; Bygdøy alle 2, P.O. Box
2464 Solli, N-0202 Oslo (NO).

(72) Inventors; and

(75) Inventors/Applicants (for US only): STEVENS, Rob
[NL/NL]; Geelgors 4, NL-6451 LH Schinveld (NL). VAN-
MARCKE, Luc [BE/BE]; Gravin d'Alcantaralaan 25,
B-9971 Kaprijke-Lembeke (BE). ELDERSON, Roeland
[NL/NL]; V. Gistellelaan 37, NL-4571 EG Axel (NL).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE,
SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA,
GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: SPRAYING DEVICE AND METHOD FOR FLUIDISED BED GRANULATION



(57) Abstract: The invention concerns a spraying device for melt granulation in fluidised bed comprising a nozzle (2) with a feed channel for a liquid to be atomised, where the liquid is led through emulsifying means and into an internal mixing chamber for gas and liquid, before it is fed to the fluidised bed. The nozzle has a separate channel for the atomising gas fitted concentrically around the central liquid supply channel for the liquid to be atomised or nebulised. The mixing chamber surrounds the outlet zone of the liquid spray from the emulsifying means and the gas, allowing efficient mixing of high speed atomising gas and liquid, and having an external gas cap (1) where fluidisation gas is channelled into a spout above the spraying device.

ATTACHMENT "F"